



Texol Multisyn™ 0W-30

Technical Data Sheet

Texol Multisyn™ 0W-30

Super high performance synthetic engine lubricant

Product description

Texol Multisyn™ 0W-30 is a super high performance synthetic, high ash, high TBN engine lubricant designed for use in gasoline and diesel passenger cars and light duty diesel vans. Texol Multisyn™ 0W-30 meets the latest ACEA A5/B5 specification and a number of critical OEM requirements.

Texol Multisyn™ 0W-30 is formulated with premium base oils in combination with an advanced additive package and a high performance viscosity improver to offer improved fuel economy with low temperature engine protection and higher lubricant durability.

Customer benefits

- Especially designed to provide enhanced fuel economy in vehicles where 0W-30 engine lubricants are recommended
- Advanced keep-clean additive package offers reliable oxidation control and acid neutralisation, helping extend engine life
- Super high performance formulation promotes robust engine wear protection under severe operating conditions
- Advanced synthetic lubricant formulation offers optimum engine uptime throughout extended drain service life
- Premium base oil and advanced additive combination promotes durable TBN retention and viscosity increase control
- Low temperature fluidity aids rapid lubricant circulation at cold start-ups, and offers increased protection where biodiesel is used

Applications

- Texol Multisyn™ 0W-30 is suitable for use in gasoline and diesel passenger cars and light duty diesel vans

Specifications

Certified against:	ACEA C3 (includes C2) ACEA A5/B5
Licensed as:	API SN
Daimler	MB 229.31, MB 229.51, MB 229.52
Volkswagen	VW 504.00 / 507.00
Porsche	C30



Texol Multisyn™ 0W-30

Technical Data Sheet

Texol Multisyn™ 0W-30

Super high performance synthetic engine lubricant

Typical Properties

Property (Unit)	0W-30	Method
Density at +15 °C	845	ASTM D4052
Viscosity @40°C, cSt	72	ASTM D445
Viscosity @100°C, cSt	12.7	ASTM D445
Viscosity Index	174	ASTM D2270
Flash Point, °C	238	ASTM D92
Pour Point, °C	-39 max	ASTM D97

Technical Expertise

Texol experts on Texol Multisyn™ series lubricants are regionally located to respond to your needs. Whether you have a question about products, applications or regulations, Texol offers comprehensive customer and technical service.