



Texol Multisyn™ TF 10W-40

Technical Data Sheet

Texol Multisyn™ TF 10W-40

Proven performance heavy-duty transmission and drive train fluids STOU

Product description

Texol Multisyn™ TF (TorqForce) 10W-40, Super Tractor Oil Universal (STOU) is a premium multi-functional oil specially formulated for use in agricultural equipment, engines, transmissions, and differentials with wet brake system and integrated hydraulic system.

Texol Multisyn™ TF (TorqForce) 10W-40, Super Tractor Oil Universal (STOU) can be used for total tractor lubrication and is specifications by many tractor manufacturers.

Customer benefits

- Texol Multisyn™ TF (TorqForce) 10W-40, Super Tractor Oil Universal (STOU) is specially formulated for agricultural use, adjusted to different circumstances like low speed/high torque etc. The carefully chosen base oils and additive system (TFAS – Texol Fluid Additive System) form a protective oil film for all the tractor components.
- Texol Multisyn™ TF (TorqForce) 10W-40, Super Tractor Oil Universal (STOU) is detergent and dispersant additives keep the engines, gearbox, differential, and hydraulic system clean and in good condition. The oil is resistant against moist and oxidation.
- Texol Multisyn™ TF (TorqForce) 10W-40, Super Tractor Oil Universal (STOU) is thermal and oxidation stable oil film. Special extreme pressure additives protect the tractor components against break down.
- Texol Multisyn™ TF (TorqForce) 10W-40, Super Tractor Oil Universal (STOU) can be used for engine, gearbox, differential and hydraulic system. A real multi purpose use.

Applications

- Total tractor lubrication, engine, gearbox, differential, hydraulic system
- Suitable for use in implements
- Tractors with wet brake system
- Power take-offs
- Earthmoving machines
- Combines
- Forklifts
- Available in 10W-30, 10W-40 and 15W-40



Texol Multisyn™ TF 10W-40

Technical Data Sheet

Texol Multisyn™ TF 10W-40

Proven performance heavy-duty transmission and drive train fluids STOU

Typical Properties

Property (Unit)	TF 10W-40	Method
Density at +15 °C	872	ASTM D4052
Viscosity @40°C, cSt	89	ASTM D445
Viscosity @100°C, cSt	13.5	ASTM D445
Viscosity Index	155	ASTM D2270
Flash Point, °C	225	ASTM D92
Pour Point, °C	-37	ASTM D97
Sulphated Ash, %wt	1.10	ASTM D874
TBN, mg KOH/g	10,5	ASTM D2896

Specifications

Multisyn™ TF 10W-40 meets:

- API CF-4/SF
- API GL-4
- MF M1144, M1145
- Ford M2C-134A, 159 B, 159C
- Ford NH 82009203
- John Deere J27
- ZF TE-ML 05K, 06B, 06C, 07B, 07D
- Allison C4

Technical Expertise

Texol experts on Texol Multisyn™ series lubricants are regionally located to respond to your needs. Whether you have a question about products, applications or regulations, Texol offers comprehensive customer and technical service.