



Texol FG Grease™ WF Series

Technical Data Sheet

Texol FG Grease™ WF Series

Aluminum complex soap synthetic food machinery grease

Product Description

Texol FG Grease WF Series, heavy-duty, extreme pressure grease made exclusively from ingredients approved by the FDA.

Texol FG Grease WF Series are engineered for use when industry demands a heavy-duty extreme pressure grease. It is available in five (5) consistencies. It contains an extreme pressure additive system along with excellent oxidation and corrosion inhibitors for applications in the “clean” industries such as food, beverage, pharmaceutical and personal care products.

Texol FG Grease WF Series, formulated with the highest quality ingredients, meets InS Service H1 and FDA requirements for materials that may have incidental contact with food as defined under Title CFR, 178.3570.

Applications and Uses

- Plain and anti-friction bearings
- Lightly loaded gears
- Extreme pressure applications
- Wet and wash-down areas

Advantages

- InS Service H1 registered
- Extremely waterproof
- Mechanically stable
- Wide temperature range
- Mild extreme pressure properties
- Excellent anti-wear properties



Texol FG Grease™ WF Series

Technical Data Sheet

Texol FG Grease™ WF Series

Aluminum complex soap synthetic food machinery grease

Characteristics

Property (Unit)	000	00	0	1	2	Method
NLGI grade	000	00	0	1	2	DIN 51 818
Base oil viscosity at 40°C	260	260	260	260	260	DIN 51 562
Colour	white					
Dropping point °C	>250					DIN ISO 2176
Four Ball weld point, N	3500					DIN 51 562
Operating temp range, °C	-45 to +160					

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can no be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.