



Texol Grease™ EP 1000 Series

Technical Data Sheet

Texol Grease™ EP 1000 Series

Synthetic lithium complex soap grease

Product Description

Texol Grease EP 1000 series are especially used for the lubrication of mechanically and thermally extreme-loaded roller and sliding bearings, wheel hubs and release bearings of couplings. It complies to the requirement TL 9150-0075/2 and is approved according to the Code Grease EP 1000. Due to its content of synthesis oil based on polyalkyleneglycol. Texol Grease EP 1000 offers longer service lives compared to mineral oil based greases. Thus, the additional lubrication intervals can be prolonged which in consequence reduces the consumption of Grease.

Applications and Uses

- Plain and anti-friction bearings
- Lightly loaded gears
- Extreme pressure applications
- Wet and wash-down areas
- Classification ISO-L-XCEHB 2 as per ISO/DIS 6743-9
- Classification KP 2 P-30 as per DIN 51 502

Advantages

- Excellent thermal stability
- Optimum wear protection
- Low coefficients of friction, low temperature rise in the bearing
- Extreme structural stability
- Resistant to cold and hot water
- Long-term stability
- High corrosion protection

Characteristics

Property (Unit)	1000-00	1000-0	1000-1	1000-2	Method
NLGI grade	00	0	1	2	DIN 51 818
Base oil viscosity at 40°C	1000	1000	1000	1000	DIN 51 562
Colour	Yellow				
Dropping point °C	>220				DIN ISO 2176
Four Ball weld point, N	6000				DIN 51 562
Pour Point, °C	< -42	< -40	< -40	< -40	DIN ISO 3016

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can no be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.