



Texol Grease™ Moly EP 2

Technical Data Sheet

Texol Grease™ Moly EP 2

High temperature grease for long-term lubrication

Product Description

Texol Grease Moly EP 2 is high performance Grease for long-term lubrication of rolling and sliding bearings at high operating temperatures as well as at normal or medium bearing pressures.

Texol Grease Moly EP 2 has a dark color due to the molybdenum disulphide contained in it. It features an even higher load bearing capacity and good emergency running properties.

Applications and Uses

- For thermally loaded rolling and sliding bearings such as fan bearings in the textile, wood, plastics and food industries as well as in stove furnaces of the automotive industry
- For steam-heated calender or drying cylinder bearings
- As sealing Grease for labyrinth seals at high temperatures
- High-speed electric motors, free-wheels
- For the application in slightly acidic or alkaline atmospheres
- Lubrication of buffer disks of trains
- On drive trains in the automotive industry
- Ventilators

Advantages

- Texol Chemical® - TFAS technology
- optimum wear protection in the high load range
- extremely good load bearing capacity
- especially aging and temperature-resistant
- structurally stable
- resistant to cold and hot water, limited resistance to alkalis and acids
- excellent corrosion protection
- pumpable in central lubrication systems
- temperature application range: - 35°C to + 180°C. In case of life-lubricated bearings the temperature of + 200°C under normal conditions should not be exceeded. Short-term operation at higher temperatures is possible – please consult our Technical Service.



The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can no be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.



Texol Grease™ Moly EP 2

Technical Data Sheet

Texol Grease™ Moly EP 2
High temperature grease for long-term lubrication

Characteristics

Base oil viscosity at 40°C	300 mm ² /s	DIN 51562
Thickening agent	Lithium complex	
Operating temperature range °C	-35 up to +180	
Colour	Black	visual
Dropping point °C	none	DIN ISO 2176
NLGI class	2	DIN 51818



The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can no be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.